



Aluminium Curtain Wall

EI 30, EI 60

with IGU (Insulated Glass Unit)


Serie 15 – EI 30, EI 60 system Curtain Wall from W.M.K. SECUR

SECUR ALU Serie 15 from W.M.K. SECUR is a complete profile system with accessories for fixed partitions formed with aluminium profiles EN AW-6060 aluminium alloy AlMgSi0,5 and core profile of steel.

Dry glazing system with EPDM gaskets and with clip on glazing beads

To prevent passage of smokes, heat and flames it is necessary to install the intumescent strips to seal perfectly the gap between the frame and the glass. Depending on the fire requirement.

Range of application: internal and external.




EI 30 fire rated glass with IGU



EI 60 fire rated glass with IGU

Secur ALU Serie 15 Curtain Wall EI 30, EI 60 with IGU



KEY

- | | | |
|---------------------------------|----------------------|------------------------------------|
| ① Aluminium Profile | ② Steel Profile | ③ EW glass with IGU |
| ④ Glazing Beads | ⑤ Gasket Beads | ⑥ Hollow Chamber for reinforcement |
| ⑦ Fireproof insulating material | ⑧ intumescent strips | |

Aluminium Curtain Wall EI 30, EI 60 with IGU

Main Technical Features:


- Aluminium profiles EN AW – 6060, aluminium alloy AIMgSi0,5 and core profile of fiberglass reinforced resin.

Main Finishes:

- Powder coated
- Anodized




Application example



Application example

POSSIBLE APPLICATIONS CHART



| SECUR ALU Serie 15 | |
|------------------------|--|
| FINISHING MATERIAL | |
| ✓ | Lacquered Aluminium |
| ✓ | Anodized Aluminium |
| ✓ | Lacquered Imitation Wood |
| THERMAL BRIDGE RUPTURE | |
| ✓ | Without thermal break** |
| | With thermal break |
| FIRE PROTECTION | |
| | EW 30 |
| | EW 60 |
| | EW 90 |
| | EW 120 |
| ✓ | EI 30 |
| ✓ | EI 60 |
| | EI 90 |
| | EI 120 |
| SYSTEMS | |
| | Fixed Partition |
| | Door |
| | Anti-trap system |
| ✓ | Mixed elements |
| | Horizontal systems |
| ✓ | Curtain Wall |
| DESIGN OPTIONS | |
| | Concealed barrel hinge |
| | Screw on hinge |
| | Door top closer |
| | Door floor closer |
| | Concealed top closer |
| | Integrated Selector |
| | Electrical latch and lock |
| | Antipanic push bar recessed |
| | Antipanic push bar overlapping |
| | Handle |
| | Push handle |
| | Retainer floor |
| | Retainer wall |
| | Retainer integrated |
| | Drop Sealant |
| ** | however, only screw from outside to inside at a distance of 250 mm |
| AUTOMATION | |
| | Access control |
| | Automatic opening |